

### In the Claims

Please cancel claims 2-4, 21-23, and 27.

Please amend the claims as follows:

1. (Currently Amended) A method for determining a specification guardband for a product used in a system comprising the steps of:  
creating a set of distribution models representative of variables that affect said specification, the set comprising models for the system on which the product is used and system to tester offset for a test system on which the specification guardband is used;  
analyzing the set of models with a statistical tool that can work with the distribution models; and  
selecting a guardband for said specification based on the statistical analysis and a tolerance target for the said specification under analysis.
- 2-4. (Cancelled)
5. (Original) The method of claim 1 where the statistical tool uses a Monte Carlo analysis.
6. (Previously amended) The method of claim 1 where a product specification is maximum frequency.

7. (Original) The method of claim 1 where a sample chosen for creating the models is at least 10.

8. (Original) The method of claim 1 where the tolerance target is a quality target.

9. (Original) The method of claim 1 where the tolerance target is a revenue target.

10. (Original) The method of claim 1 where one of the set of models is a reliability wearout model.

11. (Original) The method of claim 1 where student-t and chi-squared distribution models are used.

12. (Currently amended) ~~The method of claim 2 where the step of creating a set of models includes the additional steps of:~~ A method for determining a specification guardband for a product used in a system comprising the steps of:  
creating a set of distribution models representative of variables that affect said specification, the set comprising models for the system on which the product is used;  
analyzing the set of models with a statistical tool that can work with the distribution models;  
selecting a guardband for said specification based on the statistical analysis and a tolerance target for the said specification under analysis;  
setting up the system environment;

modeling system variables distributions during normal operation;  
setting initial system variables;  
booting the system at increasing frequencies until the system hangs;  
running system applications at the highest frequency at which the system functions and  
record such frequency; and  
changing the initial system variables and performing on new system variables the steps of  
booting and running applied to the initial system variables.

13. (Currently amended) ~~The method of claim 3 where the creating a set of models~~  
~~includes the additional steps of:~~ A method for determining a specification guardband for  
a product used in a system comprising the steps of:  
creating a set of distribution models representative of variables that affect said  
specification, the set comprising models for the system on which the product is used and  
system to tester offset for a test system on which the specification guardband is used;  
analyzing the set of models with a statistical tool that can work with the distribution  
models;  
selecting a guardband for said specification based on the statistical analysis and a  
tolerance target for the said specification under analysis;  
inputting tester to system correlation data;  
calculating system to tester offset for a set of samples;  
choosing an appropriate distribution model for the tester to system offset and  
calculating a tester to system mean and sigma based on a sample size.

14. (Currently Amended) ~~The method of claim 4 where the step of creating a set of models includes the additional steps of:~~ A method for determining a specification guardband for a product used in a system comprising the steps of:  
creating a set of distribution models representative of variables that affect said specification, the set comprising the system on which the product is used and the test system on which the guardband is used;  
analyzing the set of models with a statistical tool that can work with the distribution models;  
selecting a guardband for said specification based on the statistical analysis and a tolerance target for the said specification under analysis;  
characterizing tester system electrical and mechanical parameters that affect specifications under analysis;  
characterizing tester system to tester system offset;  
choosing an appropriate distribution model for said tester system parameters; and  
tester system offset.

15. (Original) The method of claim 12 where system variable distributions are power supply voltage and operating temperature.

16. (Currently amended) The method of claim 13~~2~~ where the step of calculating the tester to system mean and sigma is applied to a different speed sort.

17. (Original) The method of claim 13 where the method of calculating tester to system mean and sigma is applied to a different system.

18. (Original) The method of claim 14 where tester system electrical parameters are tester timing accuracy, clock edge placement accuracy and tester power supply distributions.

19. (Original) The method of claim 14 where tester system mechanical parameters are device under test interface board, tester temperature and tester handler distributions.

20. (Currently amended) A program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform method steps for determining a tester guardband for a product used in a system, the method comprising the steps of:

creating a set of distribution models representative of environmental variables for a tester and the product-under test, the set of models based on a product parameter variables that affect a specification, the set comprising the system on which the product is used and system to tester offset for the test system on which the specification guardband is used;

analyzing the set of models with a statistical tool that can work with the distribution models; and  
selecting a guardband for the tester said specification based on the statistical analysis and a tolerance target for the product under test said specification under analysis.

21-23 (Cancelled)

24. (Original) The program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform method steps for determining a tester guardband, of claim 20 wherein the program of instruction provides that one of the set of models is a reliability wearout model.

25. (Original) The program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform method steps for determining a tester guardband, of claim 20 wherein the program of instruction includes statistical program tool that uses a Monte Carlo analysis.

26. (Original) The program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform method steps for determining a tester guardband, of claim 20 wherein the program of instruction provides that the models are student-t and chi-squared distribution models